

AMENDMENTS TO THE CLAIMS

Claims 1 – 15 (previously cancelled)

16. (previously amended) A method of producing a laminated package with an opening that is sealed by a tear-off strip, said method comprising the steps of:

punching out said opening in a packaging material;

coating said packaging material at least in the area of said opening;

creating a package sleeve from said packaging material;

conveying said package sleeve onto a ^{the new matter?} (non-rotating mandrel) of a mandrel

wheel upstream from a filling machine for filling said laminated package; and

attaching said tear-off strip to said opening in said package sleeve,

wherein said tear-off strip is attached at said mandrel of said mandrel

wheel.

17. (previously amended) A method according to Claim 16, wherein said package sleeve is conveyed to said filling machine in such a way that its opening points outward across the working direction of said filling machine.

18. (previously amended) A method according to Claim 16, wherein said package sleeve is rotated about its longitudinal axis by approximately 90°

between a magazine for accommodating prefabricated package sleeves on said filling machine and the location where said tear-off strip is attached.

19. **(previously amended)** A method according to Claim 16,
wherein said mandrel wheel is driven in cycles and has at least two
mandrels; and
wherein said tear-off strip is applied using at least one welding device
which is inserted between said two mandrels and is retracted again after said
tear-off strip has been welded.

20. **(previously amended)** A method according to Claim 16, wherein said
tear-off strip or a pouring element is applied upstream from an aseptic station of
said filling machine.

21. **(previously amended)** A method according to Claim 16, wherein said
tear-off strip or a pouring element is attached by welding.

22. **(previously amended)** A method according to Claim 21, wherein said
tear-off strip or said pouring element is attached by ultrasonic welding or high-
frequency welding.

23. **(previously amended)** A method according to Claim 16, wherein said
tear-off strip or a pouring element is attached by gluing.

24. **(previously amend d)** A method according to Claim 16, wherein said tear-off strip or a pouring element is pulled off from a supply roll having a plurality of tear-off strips or pouring elements.

25. **(previously amended)** A method according to Claim 24, wherein said tear-off strip or said pouring element is conveyed by means of feed rollers and is detached from said supply roll by a cutting device.

26. **(previously amended)** A method according to Claim 16, wherein said tear-off strip consists of a tear-resistant aluminum strip.

27. **(previously amended)** A method according to Claim 16, wherein said filling machine is a filling machine having multiple lanes.

28. **(previously added)** A laminated package having an opening that is sealed by a tear-off strip, as produced by the method of Claim 16.

29. **(previously added)** A method of producing a laminated package with an opening that is sealed by a tear-off strip, said method comprising the steps of:

punching out said opening in a packaging material;

coating said packaging material at least in the area of said opening;

creating a package sleeve from said packaging material;
conveying said package sleeve onto a non-rotating mandrel of a mandrel wheel upstream from a filling machine for filling said laminated package; and
attaching said tear-off strip to said opening in said package sleeve,
wherein said package sleeve is rotated about its longitudinal axis by approximately 90° between a magazine for accommodating prefabricated package sleeves on said filling machine and the location where said tear-off strip is attached.

30. **(previously added)** A method of producing a laminated package with an opening that is sealed by a tear-off strip, said method comprising the steps of:

punching out said opening in a packaging material;
coating said packaging material at least in the area of said opening;
creating a package sleeve from said packaging material;
conveying said package sleeve onto a mandrel of a mandrel wheel driven in cycles having at least two mandrels upstream from a filling machine for filling said laminated package; and
attaching said tear-off strip to said opening in said package sleeve,
wherein said tear-off strip is applied using at least one welding device which is inserted between said two mandrels and is retracted again after said tear-off strip has been welded.

31. (new) A method of producing a laminated package with an opening that is sealed by a tear-off strip, said method comprising the steps of:

punching out said opening in a packaging material;

coating said packaging material at least in the area of said opening;

creating a package sleeve from said packaging material;

conveying said package sleeve onto a ^{the new method} non-rotating mandrel of a mandrel wheel upstream from a filling machine for filling said laminated package; and

attaching said tear-off strip to said opening in said package sleeve,

wherein said tear-off strip is attached with the help of an anvil when said package sleeve is in the region of a pocket of a pocket conveyor.
